PERSONA Campus Online Version 7.0 Server Requirements

System with Local Database	System with Remote Database
Up to 500 Locks: • Memory: 4 GB minimum, 8 GB+ recommended • Processor: 2 GHz or faster Dual-core minimum • Storage: 50 GB (additional space as needed)	
 500 to 1000 locks: Memory: 8 GB minimum Processor: 2 GHz or faster 4 cores minimum Storage: 50 GB (additional space as needed) 	 Memory: 4 GB minimum, 8 GB+ recommended Processor: 2 GHz or faster Dual-core minimum Storage: 25 GB Minimum
For systems with more than 1000 locks it is recommended to move the database to a remote server	

• Supported Databases: Microsoft SQL Server 2012 to 2019

Installed with Mixed Mode authentication enabled as installer requires a SQL sysadmin account.

• Supported Operating Systems:

•

Windows 10 Pro & Enterprise (Home editions of Windows are not supported)* Windows Server 2012, 2012R2, 2016 & 2019

Installation Prerequisites

Microsoft IIS with:

Common HTTP Features: Default Document Directory Browsing HTTP Errors Static Content

Application Development Features: .NET Extensibility 4.6 & 3.5 ASP.NET 4.6 ISAPI Extensions ISAPI Filters WebSocket Protocol

Aperio Gateway Inbound TCP Ports:

• 9999 - Aperio Hubs

• 5021 – PERSONA Server

Firewall Requirements

PERSONA Server Inbound TCP Ports:

- 2571 IP Enabled Locksets
- 4070 VertX & Edge Controllers
- 443 & 8333 Aperio Gateway
- Port 80 or 443 Web client

• Dependent on if site has applied SSL

VertX Inbound TCP Ports:

• 80 – PERSONA Server

Browser Requirements

Microsoft Edge, Chrome, Firefox, and Safari (on iOS only) are supported NOTE: Microsoft Internet Explorer is not supported.

NOTES:

- * If installed on a workstation operating system, IIS limits the number of concurrent requests and is not recommended in a
 production environment.
- SQL Express may be used with less than 500 locksets. A full SQL license is recommended for larger or interfaced sites.
- Windows Installer 4.6 & .NET Framework 4.6 will be installed or upgraded during install.

69 – Aperio Gateway Firmware updates only

Aperio Hub Inbound UDP Port